



PLUTON 9202



Fût rond-conique en aluminium, en 2 éléments emboîtés avec système de blocage, 60 mm en tête.
Avec renforts, entraxe 300 mm.
Round conical aluminium pole, in 2 slip jointed elements with anti-rotating device, 60 mm at top.
With reinforcement, Fixing bolts centers : 300 mm.

								
10	60 x 200	600 x 120	600	115 x 130	300	25/24 x 600	80	
11	60 x 200	600 x 120	600	115 x 130	300	25/24 x 600	83	
12	60 x 200	600 x 120	600	115 x 130	300	25/24 x 600	93	
13	60 x 200	600 x 120	600	115 x 130	300	25/24 x 600	96	
14	60 x 200	600 x 120	600	115 x 130	300	25/24 x 600	106	
15	60 x 200	600 x 120	600	115 x 130	300	25/24 x 600	109	

			24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
10	40		1,03	0,84	0,85	0,7	0,71	0,58	0,6	0,48	0,43	0,34	2029	295	0.5 x 1.2
11	40		0,62	0,51	0,51	0,41	0,42	0,34	0,35	0,28	0,25	0,2	1959	283	0.5 x 1.2
12	40		0,59	0,47	0,47	0,37	0,38	0,29	0,3	0,23	0,2	0,13	2034	291	0.5 x 1.2
13	40		0,33	0,26	0,25	0,2	0,2	0,15	0,15	0,11	0,09		2036	291	0.5 x 1.2
14	20		0,35	0,27	0,26	0,19	0,2	0,13	0,14	0,08	0,06		2037	291	0.5 x 1.2
15	20		0,16	0,11	0,1	0,06	0,07						0	0	0.5 x 1.2