



VENUS 9145



Fût rond-conique en aluminium,
60 mm en tête.
Type SR- M2 : sans renfort, entraxe 200 mm
Type AR- M3 : avec renforts, entraxe 300 mm.
*Round conical aluminium pole,
60 mm at top.*
SR- M2 : without reinforcement, fixing bolts centers : 200 mm
AR- M3 : with reinforcement, fixing bolts centers 300 mm.

								
SR-M2	3,5	60 x 145	500 x 100	600	80 x 105	200	16/14 x 300	17
SR-M2	4	60 x 145	500 x 100	600	80 x 105	200	16/14 x 300	19
SR-M2	4,5	60 x 145	500 x 100	600	80 x 105	200	16/14 x 300	20
SR-M2	5	60 x 145	500 x 100	600	80 x 105	200	16/14 x 300	21
SR-M2	6	60 x 145	500 x 100	600	80 x 105	200	16/14 x 300	24
AR-M3	6	60 x 145	500 x 100	600	80 x 105	300	20/18 x 400	29

		24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
3,5	40	1	0,82	0,84	0,68	0,71	0,59	0,61	0,5	0,46	0,38	355	123	0.4 x 0.5
4	40	0,78	0,6	0,65	0,5	0,54	0,42	0,46	0,36	0,34	0,27	348	113	0.4 x 0.5
4,5	40	0,58	0,45	0,47	0,36	0,39	0,3	0,33	0,25	0,24	0,18	345	106	0.4 x 0.5
5	40	0,42	0,32	0,34	0,26	0,28	0,2	0,23	0,17	0,16	0,12	343	103	0.4 x 0.5
6	40	0,2	0,14	0,15	0,1	0,11	0,07	0,08				342	100	0.4 x 0.5
6	40	0,26	0,2	0,21	0,16	0,17	0,13	0,14	0,11	0,1	0,08	620	146	0.5 x 0.6