



BA 2120

SA : sans accès / *without access*
AA : avec accès / *with access*
1P : 1 porte / *1 door*
2P : 2 portes / *2 doors*



Fût octo-conique en acier,
120 mm sur plats en tête, 2 rangées d'écrous soudés à 100 et 600 mm du sommet.
Octagonal conical steel pole,
At top 120 mm across flats, 2 rows of welded nuts at 100mm and 600 mm from top.

								
SA 1P	9	120 x 230	600 x 135	500	135 x 155	300	25/24 x 600	200
AA 2P	10	120 x 230	600 x 135	500	135 x 155	300	25/24 x 600	212
SA 1P	11	120 x 252	600 x 135	500	135 x 185	300	25/24 x 600	256
SA / AA 2P	12	120 x 252	600 x 135	500	135 x 185	300	25/24 x 600	276
SA / AA 2P	14	120 x 252	600 x 135	500	135 x 185	300	25/24 x 600	311

		24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
9	100	2,98	2,39	2,44	1,93	2	1,59	1,66	1,29	1,16	0,87	3920	630	0.7 x 1.5
10	100	2,32	1,83	1,86	1,47	1,49	1,16	1,22	0,92	0,79	0,56	3928	619	0.7 x 1.5
11	100	2,49	2	2,03	1,56	1,61	1,25	1,29	0,98	0,83	0,57	4805	704	0.7 x 1.5
12	100	2	1,54	1,56	1,18	1,21	0,89	0,94	0,66	0,53	0,31	4806	703	0.7 x 1.5
14	100	1,22	0,89	0,88	0,6	0,62	0,38	0,41	0,2	0,1		4800	660	0.7 x 1.5

BA 2462



Fût octo-conique en acier,
62 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.
Octagonal conical steel pole,
62 mm at top, 2 rows of threaded holes at 100 and 200 mm from top.

10	60 x 230	600 x 135	500	135 x 155	300	25/24 x 600	150
12	60 x 230	600 x 135	500	135 x 155	300	25/24 x 600	180

		24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
10	100	2,05	1,64	1,66	1,32	1,34	1,05	1,11	0,84	0,73	0,53	3448	556	0.7 x 1.5
12	100	1,25	0,96	0,96	0,72	0,73	0,53	0,56	0,37	0,28	0,14	3454	562	0.7 x 1.5