














OLERON 2489

Fût rond-conique en acier, en 2 éléments emboîtés,
89 mm en tête, 2 rangées de crevés taraudés à 100 et 450 mm du sommet.
*Round conical steel pole, 2 slip jointed parts,
89 mm at top, 2 rows of threaded holes at 100 and 450 mm from top.*

								
14	89 x 261	600 x 140	500	160 x 175	300	D25/24 x600	311	
15	89 x 274	600 x 140	500	200 x 150	300	D32/30 x1070	351	
16	89 x 287	600 x 140	500	200 x 170	300	D32/30 x1070	373	
18	89 x 313	600 x 140	500	200 x 180	400	D32/30 x1070	465	

			24m/s		26m/s		28m/s		30m/s		34m/s		M	T	
			Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
14	100		1,59	1,32	1,32	1,09	1,1	0,89	0,92	0,73	0,64	0,49	4640	510	0.7 x 1.5
15	100		1,61	1,34	1,32	1,1	1,1	0,89	0,92	0,73	0,62	0,47	5229	552	0.7 x 1.5
16	100		1,61	1,34	1,32	1,09	1,09	0,88	0,9	0,71	0,6	0,44	5796	593	0.9 x 1.8
18	100		2,03	1,73	1,71	1,47	1,44	1,22	1,22	1,04	0,9	0,76	9507	812	1.1 x 2.2