



SECURIMAT

Fût rond- conique en acier.
Fût à sécurité passive (type absorption d'énergie),
60 mm en tête, 2 rangées de crevés taraudés à 100 et 200 mm du sommet.
Round conical steel pole.
Passive safety mast (energy absorbing type),
60 mm at top, 2 rows of threaded holes at 100 and 200 mm from top.

							
6	60 x 145	405 x 95	490	85 x 85	200	16/14 x 300	42
8	60 x 170	405 x 100	490	95 x 110	300	20/18 x 400	74
10	60 x 195	405 x 103	490	95 x 140	300	20/18 x 400	93

		24m/s		26m/s		28m/s		30m/s		34m/s		M		
		Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	Cat II	Cat I	m.daN	daN	
6	50	0,51	0,39	0,4	0,3	0,32	0,24	0,26	0,19	0,17	0,13	534	133	0.5 x 0.6
8	50	0,38	0,28	0,29	0,2	0,22	0,15	0,17	0,11	0,1	0,07	769	158	0.6 x 0.7
10	50	0,29	0,2	0,21	0,14	0,15	0,1	0,11	0,07			1044	193	0.5 x 0.9